

Tapered roller thrust bearing TTC, TTCS, TTCL series

		Dimensions(mm/in.)					Steering Pivot Rating(N/lbf)	Bearing Weight(kg/lbs.)
No Oil Holes In Retainer	Oil Holes In Retainer	Fig.	:	:	T	R		
T127	T127W	C	32.004	66.675	19.446	0.8	42200	0.31
T127		C	1.26	2.625	0.7656	0.03	9450	0.68
T128		D	32.004	66.675	18.654	0.8	42200	0.29
T128		D	1.26	2.625	0.7344	0.03	9450	0.64
T130		C	27.102	66.675	19.446	0.8	42200	0.34
T130		C	1.067	2.625	0.7656	0.03	9450	0.75
T136		D	35.179	66.675	18.654	0.8	42200	0.28
T136		D	1.385	2.625	0.7344	0.03	9450	0.62
T138	T138W	C	35.179	66.675	19.446	0.8	42200	0.30
T138		C	1.385	2.625	0.7656	0.03	9450	0.66
T138XS		SPCL(1)	35.179	66.675	19.446	0.8	42200	**
T138XS		SPCL(1)	1.385	2.625	0.7656	0.03	9450	0
T144	T144W	C	36.754	66.675	19.446	1.5	42200	0.29
T144		C	1.447	2.625	0.7656	0.06	9450	0.64
T144XA		SPCL(1)	36.754	66.675	19.446	1.5	42200	**
T144XA		SPCL(1)	1.447	2.625	0.7656	0.06	9450	0
T151	T151W	C	38.354	72.619	21.433	0.8	47000	0.37
T151		C	1.51	2.859	0.8438	0.03	10600	0.82
T152		D	38.354	72.619	20.638	0.8	47000	0.35
T152		D	1.51	2.859	0.8125	0.03	10600	0.77
T157	T157W	C	39.954	72.619	21.433	0.8	47000	0.37
T157		C	1.573	2.859	0.8438	0.03	10600	0.82
T163	T163W	C	41.529	72.619	21.433	0.8	47000	0.35
T163		C	1.635	2.859	0.8438	0.03	10600	0.77
T163X	T163XW	C	41.529	72.619	21.433	2.0	47000	0.35
T163X		C	1.635	2.859	0.8438	0.8	10600	0.77

Tapered roller thrust bearing TTC, TTCS, TTCL series

T169	T169W	C	43.104	82.956	23.812	0.8	64000	0.55
T169		C	1.697	3.266	0.9375	0.03	14300	1.21
T176	T176W	C	44.704	82.956	23.812	0.8	64000	0.54
T176		C	1.76	3.266	0.9375	0.03	14300	1.19