

Thin Section Bearings

지정	다:	다:	d1	D1	r	비:	B1	Dw	t	A	A1
CSCC040	101.6 mm	120.65 mm	108.6 mm	113.6 mm	1	9.525	4.1	4.763	35	7.7	0.9
CSCB080	203.2 mm	219.075 mm	209.1 mm	213.2 mm	1	7.937	3.43	3.969	83	6.4	0.8
CSCB070	177.8 mm	193.675 mm	183.7 mm	187.8 mm	1	7.937	3.43	3.969	73	6.4	0.8
CSCB065	165.1 mm	180.975 mm	171 mm	175.1 mm	1	7.937	3.43	3.969	68	6.4	0.8
CSCB060	152.4 mm	168.275 mm	158.3 mm	162.4 mm	1	7.937	3.43	3.969	63	6.4	0.8
CSCB050	127 mm	142.875 mm	132.9 mm	137 mm	1	7.937	3.43	3.969	53	6.4	0.8
CSCB045	114.3 mm	130.175 mm	120.2 mm	124.3 mm	1	7.937	3.43	3.969	48	6.4	0.8
CSCB042	107.95 mm	123.825 mm	113.8 mm	117.9 mm	1	7.937	3.43	3.969	45	6.4	0.8
CSCB040	101.6 mm	117.475 mm	107.5 mm	111.6 mm	1	7.937	3.43	3.969	43	6.4	0.8
CSCB035	88.9 mm	104.775 mm	94.8 mm	98.9 mm	1	7.937	3.43	3.969	38	6.4	0.8
CSCB030	76.2 mm	92.075 mm	82.1 mm	86.2 mm	1	7.937	3.43	3.969	33	6.4	0.8
CSCB025	63.5 mm	79.375 mm	69.4 mm	73.5 mm	1	7.937	3.43	3.969	28	6.4	0.8
CSCB020	50 mm	66.675 mm	56.7 mm	60.8 mm	1	7.937	3.43	3.969	23	6.4	0.7
CSCAA017TN	44.45 mm	53.975 mm	48 mm	50.4 mm	0.38	4.762	2	2.381	0.8	3.5	0.6
CSCAA015TN	38.1 mm	47.625 mm	41.7 mm	44.1 mm	0.38	4.762	2	2.381	0.8	3.5	0.7
CSCAA010TN	25.4 mm	34.925 mm	29 mm	31.4 mm	0.38	4.762	2	2.381	0.8	3.5	0.6
CSCA120	304.8 mm	317.5 mm	309.5 mm	312.8 mm	0.6	6.349	2.67	3.175	147	5.1	0.7
CSCA100	254 mm	266.7 mm	258.7 mm	262 mm	0.6	6.349	2.67	3.175	123	5.1	0.7
CSCA090	228.6 mm	241.3 mm	233.3 mm	236.6 mm	0.6	6.35	2.67	3.175	111	5.1	0.7

Thin Section Bearings

CSCA080	203.2 mm	215.9 mm	207.9 mm	211.2 mm	0.6	6.35	2.67	3.175	99	5.1	0.7
CSCA075	190.5 mm	203.2 mm	195.2 mm	198.5 mm	0.6	6.349	2.67	3.175	93	5.1	0.7
CSCA070	177.8 mm	190.5 mm	182.5 mm	185.8 mm	0.6	6.349	2.67	3.175	87	5.1	0.7
CSCA065	165.1 mm	177.8 mm	169.8 mm	173.1 mm	0.6	6.35	2.67	3.175	81	5.1	0.7
CSCA060	152.4 mm	165.1 mm	157.1 mm	160.4 mm	0.6	6.349	2.67	3.175	75	5.1	0.7
CSCA055	139.7 mm	152.4 mm	144.4 mm	147.7 mm	0.6	6.35	2.67	3.175	69	5.1	0.7
CSCA050	127 mm	139.7 mm	131.7 mm	135 mm	0.6	6.349	2.67	3.175	63	5.1	0.7
CSCA047	120.65 mm	133.35 mm	125.3 mm	128.6 mm	0.6	6.349	2.67	3.175	60	5.1	0.7
CSCA045	114.3 mm	127 mm	119 mm	122.3 mm	0.6	6.35	2.67	3.175	57	5.1	0.7
CSCA042	107.95 mm	120.65 mm	112.6 mm	115.9 mm	0.6	6.35	2.67	3.175	54	5.1	0.7
CSCA040	101.6 mm	114.3 mm	106.3 mm	109.6 mm	0.6	6.35	2.67	3.175	51	5.1	0.7